

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.


Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.


**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

FIG.1



2/8

FIG.2



3/8

FIG.3

step number	X(mm)	Y(mm)	θ (angle)	FDR	C
0000	+ 0.00	+ 0.00	+ 0° 00'	000	—
0001	10.00	120.00	0° 00'	101	—
0002	15.00	130.00	90° 00'	101	—
0003	20.00	150.00	0° 00'	103	—
0004	60.00	50.00	180° 00'	103	—
0005	110.00	80.00	270° 00'	105	—
0006	210.00	220.00	0° 00'	105	—
0007	310.00	120.00	180° 00'	107	—
0008	310.00	20.00	90° 00'	110	—
0009	180.00	50.00	0° 00'	110	—
0010	160.00	80.00	270° 00'	110	—
0011	290.00	220.00	0° 00'	110	—
0012	0.00	0.00	0° 00'	000	E

FIG.4

FDR NO	◀	component ID	▶	C	comment
101		C3216		—	
103		R1005		—	
105		SOP14		—	
107		QFP100-0001-0500		—	
110		VQFP48		E	

FIG.5

<COMPONENT LIBRARY EDIT> COMPONENT ID : QFP100-0001-0500 1GG1234567890123

COMPONENT ID	QFP100-0001-0500		SHAPE DATA	RECOGNITION DATA
COMMENT	1GG1234567890123			COMPONENT FEEDER DATA
COMPONENT FORM	FLAT PACKAGED			
LIGHTING MODE	REFLECTION			
NOZZLE TYPE	FIRST PREFERRED NOZZLE	MF01	VALID	SECOND PREFERRED NOZZLE
	CONTROL DATA (FIRST PREFERRED NOZZLE)		MA08	VALID
			CONTROL DATA (SECOND PREFERRED NOZZLE)	

COMPONENT ID : QFP100-0001-0500
 PLEASE INPUT THE DATA AND PRESS THE [SET] KEY.

Q	W	E	R	T	Y	U	I	O	P
A	S	D	F	G	H	J	K	L	
Z	X	C	V	B	N	M			

RETURN

BS	←	→	CHANGE	SET
----	---	---	--------	-----

FIG.6

PICK-UP RETENTION TIME	0.00 sec	SPEED DATA	BEAM(X/Y)	FULL SPEED
PLACEMENT RETENTION TIME	0.00 sec		PICK-UP DESCENT	FULL SPEED
			PICK-UP ASCENT	FULL SPEED
			PLACEMENT DESCENT	FULL SPEED
			PLACEMENT ASCENT	FULL SPEED
			NOZZLE ROTATION	FULL SPEED
			RECOGNITION TIME	0.10 sec


COMPONENT POSITION CORRECTION	X	+ 00 mm	PICK-UP LEVEL	+ 0.10 mm
	Y	+ 00 mm	PLACEMENT LEVEL	+ 0.30 mm
PICK-UP LOCATION ADJUSTMENT	X	+ 00 mm	FOCUS ADJUSTMENT	+ 0.00 mm
	Y	+ 00 mm	ERROR PROCESS DATA 1	2
AUTOMATIC FOR AXIS ADJUSTMENT	X	ON	ERROR PROCESS DATA 2	2
	Y	ON		

FIG. 7

PICK-UP RE	0.10 sec	SPEED DATA	BEAM(X/Y)	50%DECELERATION
PLACEMENT RETENTI	0.00 sec		PICK-UP DESCENT	50%DECELERATION
			PICK-UP ASCENT	50%DECELERATION
			PLACEMENT DESCENT	50%DECELERATION
			PLACEMENT ASCENT	50%DECELERATION
			NOZZLE ROTATION	50%DECELERATION
			RECOGNITION TIME	0.10 sec
COMPONENT POSITION CORRECTION	X	+ 0.0 mm	PICK-UP LEVEL	+ 0.10 mm
	Y	+ 0.0 mm	PLACEMENT LEVEL	+ 0.30 mm
PICK-UP LOCATION ADJUSTMENT	X	+ 0.0 mm	FOCUS ADJUSTMENT	+ 0.00 mm
	Y	+ 0.0 mm	ERROR PROCESS DATA 1	2
AUTOMATIC FOR AXIS ADJUSTMENT	X	ON	ERROR PROCESS DATA 2	2
	Y	ON		

FIG.8

- ① When it was changed for the first preferred nozzle.



- ② When operation was continued with the second preferred nozzle.




FIG. 9

<COMPONENT LIBRARY EDIT> COMPONENT ID : QFP100-0001-0500 1GG1234567890123

COMPONENT ID	QFP100-0001-0500
COMMENT	1GG1234567890123
COMPONENT FORM	FLAT PACKAGED
LIGHTING MODE	REFLECTION
NOZZLE TYPE	MF01

COMPONENT ID : QFP100-0001-0500

PLEASE INPUT THE DATA AND PRESS THE [SET] KEY.

Q	W	E	R	T	Y	U	I	O	P
A	S	D	F	G	H	J	K	L	
Z	X	C	V	B	N	M			

RETURN

BS	←	→	CHANGE	SET
----	---	---	--------	-----

SHAPE DATA	RECOGNITION DATA	CONTROL DATA	COMPONENT FEEDER DATA
------------	------------------	--------------	-----------------------